

MT225s PREMIUM COMPACT TRACTORS

and the state of

St aligned

LLEEOO

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT2S SERIES PREMIUM COMPACT TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER: High Capacity With An Abundance Of Standard Features



BACKHOE: Excellent Capacity, Smooth And Consistent Operation For Added Control



ROTARY CUTTER: Durable Heavy Steel Design Providing Quality And Strength



BOX BLADE: Features A Heavy Welded Steel Design For Use In Demanding Applications

FEATURES

- 🗲 6 Year Warranty*
- 🗡 24.7 HP Yanmar Diesel Engine
- 🕶 3 Range Hydrostatic Transmission (2 Pedal)
- 🛩 Electric Engagement Independent PTO
- New Heavy-Duty Platform/Frame



Premium Reversible Seat Adjustable Foldable Armrest, Tilt High Back Seat. *Reversible Seat Only On Backhoe Models



3 Range Hydrostatic
Transmission
(2 Pedal) Comfortable And
Efficient Operator Control



Bolted Edge Bucket Built For The Harshest Conditions



Standard Factory Grille Guard W/ Loader Full Length Grille Guard Protect Body Panels And Radiator



Optional Thumb Configuration Backhoe Provides Added Functionality To The Heavy-Duty Backhoe



Optional Drive-Over Mid-Mount Mower Deck Providing Convenience And Ease Of Adapting To Any Application



Standard Tilt Steering Provides Enhanced Operator Comfort



Standard Foldable ROPS Enables Easy Adjustment For Clearance



Mid-Mount Mower Height Adjustment Dial Enables Precise Height Control Of The Mid-Mount Mower, By A Simple Turn



SPECIFICATIONS

CATEGORY	
ENGINE	MT225s
Туре	3 Cylinder-IDI
Model (Tier 4)	3TNV80F-ZXKLST (Yanmar)
Engine HP (gross)	24.7
PTO (HP)	19.3
Rated Speed (rpm)	2,800
Displacement-cu (in ³ .)	77.3
FuelTank Capacity (gal.)	6.79
Alternator (V-A)	12 - 40
DRIVE TRAIN	
Transmission	HST
No. Of Speed	3 Ranges
Brakes	Wet, Multi-disc
РТО	
Туре	Independent
Rear (rpm)	540
Mid PTO (Option)	2,500
HYDRAULIC SYSTEM	
Lift Control System	Position
Implement Pump (gpm)	5.6
Steering Pump (gpm)	3.7
Steering	Hydrostatic Power Steering
Total Flow (gpm)	9.3
Category (3pt Hitch)	CAT I
Hitch Lift Capacity (Ibs.) (Hitch End)	1,896
Remote Valves	1 Pair (Option)
DIMENSION (with R1 tires)	
Overall Length (Frame To Link in.)	111.9
Overall Width With Tires (in.)	48.7
Wheelbase (in.)	63.4
Height To Top Of ROPS (in.)	86.4
TIRE SIZE	
Front / Rear Ag (R1)	7 - 12 / 11.2 -16
Front / Rear Industrial (R4)	23 x 8.5 - 12 / 12 - 16.5
Front / RearTurf (R3)	22 x 8.5 - 12 / 31 x 15.5 - 15
WEIGHT	
Total Weight w/o Ballast (lbs.)	1,764

*All Specs and features are subject to change, and pictures could include optional equipment etc.

FRONT END LOADER	LL2300
TRACTOR APPLICATION	MT225s
Bucket Size (in.)	54.3
Maximum Lift Height (in.)	84.4
Clearance With Attachment Dump (in.)	59.1
Reach At Maximum Height (in.)	17.9
Maximum Dump Angle (deg.)	55
Maximum Rollback Angle (deg.)	40
Digging Depth (in.)	4.5
Overall Heights In Carry Position (in.)	46
Lift Capacity (At Pivot Pin) (Ibs.)	1,067
Breakout Force (At Pivot Pin) (Ibs.)	2,290
Approx. Weight (Loader w/o Bucket) (lbs.)	708

BACKHOE	LB1300
TRACTOR APPLICATION	MT225s
Digging Depth (in.)	84.9
Reach From Centerline Of Swing Pivot (in.)	113.7
Loading Height (in.)	64.7
Swing Arc (deg.)	180
Transport Height (in.)	73.4
Bucket Rotating (deg.)	177
Stabilizer Spread (Down Position) (in.)	82.2
Stabilizer Spread (Up Position) (in.)	65.4
Bucket Digging Force (Ibs.)	3,013

MID MOWER	LM2360
TRACTOR APPLICATION	MT225s
Cutting Width (in.)	60
Cutting Height Range (in.)	1 - 4
Transport Height (in.)	6
GearType	Spiral Bevel
Number Of Blades	3
Adjustment Of Cutting Height	Dial
Deck Thickness (in.)	0.15
Total Width (in.)	75.7
Total Length (w/o Linkage)	44.1
Total Height (w/o Linkage)	11.9
LiftingType	3-Point Upper Link
Total Weight (Ibs.)	368

Additional Equipment

- Standard Factory Toolbox
- Standard 12 Volt Power Outlet
- Flat Operator With Rubber Mat
- Standard Factory Platform Step



LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LS Tractor USA.com (Corporate Address) 6900 Corporation Parkway, Battleboro, NC

and at her

15

Charles Provident